

MASTERPLAT

SEMI-AUTOMATIC STRETCH WRAPPER

Designed for customers wrapping up to 30 loads per hour. Includes productivity improvement standards like Self-Learning Wrap Program, 110" wrap height and a heavy duty 4,400 pound capacity turntable.

- Structural Integrity – 65" turntable with 28 support bearings.
- Maximum weight: 4400 lbs.
- Standard wrap height: 110"



Performance features:



R-CONNECT READY

Developed to provide usage and performance data via the cloud. Utilization drastically reduces downtime by giving you informational transparency, allowing you to connect with your machines remotely to investigate

CONTROL PANEL

The new control panel combines the Master Jog Dial with graphic display with intuitive icons to make it easy to set up and to select the correct wrapping parameters for each of your loads.



PGS CARRIAGE

The PGS film carriage is fixed gear 250% power pre-stretch and the force to load (tension) is controlled by a strain gauge, adjusted on the control panel.



Masterplat Specifications

Performance Criteria

Production Speed:

Up to 30 LPH

Turntable Speed:

5 – 12 RPM

Turntable Drive:

1 HP VAC

Load Handling System

Turntable Size:

65" Diameter

Maximum Load Height:

110"

Maximum Load Weight:

4400 lbs.

Film Delivery System

- Containment Force: Variable Electronic
- Film Carriage Motor: ½ HP VAC
- Height Sensing: Automatic via photocell
- Film Threading: Patented S-Pattern
- Corner Compensation: Load Cell

Safety Features

- Anti-fall device on carriage
- Pressure activated safety stop on carriage
- CE Compliant, UL, CUL

Utilities

Voltage:

115V, 20 amps, 60 Hz, 1 PH

Warranty:

3 Years

