

## ROTOPLAT 708

SEMI-AUTOMATIC STRETCH WRAPPER

The Rotoplat 708 with CUBE Technology is the most innovative stretch wrapper in the market. It is also the easiest to use, thanks to its intuitive seven (7) inch color touchscreen.

- Save 30-55% on film with Cube Technology
- Rconnect ready
- Save 6 unique load configurations
- 65" turntable with 28 support bearings
- 4400 lbs. weight capacity
- 110" standard wrap height



## Performance features:



### R-CONNECT READY

Developed to provide usage and performance data via the cloud. Utilization drastically reduces downtime by giving you informational transparency, allowing you to connect with your machines remotely to investigate

### COLOR TOUCH SCREEN

The high performance 7-inch color touch screen with icons specifically designed and created by Robopac has led to the implementation of the MULTILEVEL CONTROL function.



### PVS CARRIAGE

Powered stretch system controlled by two motors. Stretch ratio adjustable from panel board from 150-400%. Force to the load controlled by patented electronic device and adjustable from panel board.

### STAINLESS STEEL VERSION AVAILABLE

Ideal for processing, wet or cold applications., our stainless steel Rotoplat 708 stretch wrapper is designed for industries requiring high hygiene like meat, poultry, fish, dairy, beverage and wherever high food safety is essential.



### Rotoplat 708 Specifications

#### Performance Criteria

##### Production Speed:

Up to 40 LPH

##### Turntable Speed:

5 – 12 RPM

##### Turntable Drive:

1 HP VAC

#### Load Handling System

##### Turntable Size:

65" Diameter

##### Maximum Load Height:

110"

##### Maximum Load Weight:

4400 lbs.

#### Film Delivery System

- Containment Force: Multi-Level Variable
- Film Carriage Motor: ½ HP VAC
- Height Sensing: Automatic via photocell
- Film Threading: Patented S-Pattern
- Corner Compensation: Load Cell

#### Safety Features

- Anti-fall device on carriage
- Pressure activated safety stop on carriage
- CE Compliant, UL, CUL

#### Utilities

##### Voltage:

115V, 20 amps, 60 Hz, 1 PH

##### Warranty:

5 Years