



D4-e Units feature easy-to-use touchpads with bright LCD screens to allow operators to quickly setup system parameters and monitor system operation without the need to learn any confusing codes.

D4-e System touchpad PID controller features:

- graphical display/interface
- programmable sequential zone start-up
- automatic temperature setback
- high/low temperature protection
- Fahrenheit or Celsius option
- system diagnostics
- seven-day programmable clock
- two user selectable inputs and one selectable output
- password protection for setup configuration

Technical Specifications

D4-e Characteristics	
Tank Capacity:	4.0 kg
Melt Rate:	5.0 kg/hr (11.1 lbs/hr)
Motor:	1/4 HP Fixed Speed AC
Pump Rate:	27 kg/hr (60 lb/hr)
Temp. Range:	30-230°C
Temp. Stability	0.5°C
Electrical:	110/120 VAC or 200/240 VAC 20 AMP single phase with ground
Weight: (empty)	34.0 kg (75.0 lbs)
Dimensions (WxHxD):	312 mm x 424 mm x 607 mm (12.3 in x 16.7 in x 23.9 in)
Gun Attachments:	2

To learn more about how Valco Melton's EcoStitch can save your company money, contact us today!



2031 Carolina Place Drive | Fort Mill, SC 29708 | 803-831-2099
inkjetandadhesives@pak-tec.com | www.pak-tec.com