PAKTEC
PACKAGE WITH CONFIDENCE

L-SEALERS
PERFORMANCE SERIES

L-SEALERS
PERFORMANCE SERIES

RELIABLE SEMI-AUTOMATIC L-SEALING

EASTEY Performance Series L-Sealers offer the durability needed to handle a variety of applications at a cost-effective price.

MODELS
EM1622TK, EM1636TK

BUILT RIGHT...PRICED RIGHT
Proven reliable over and over again, these intermediate level EASTEY L-Sealers provide you with all the quality features found in much higher priced machines. They are designed and built to give you all the performance features needed for positive sealing a wide variety of films including polyolefin, polyethylene, and PVC.

RUGGED DESIGN
EASTEY Performance Series L-Sealers are expertly welded on 12 gauge steel frames and designed to handle the day to day abuse of manual sealing in most shrink wrap applications. Cast seal arms, stainless steel film clamps, and heavy duty dual magnet clamping are just some of the features that provide the durability you have come to rely on from EASTEY. See for yourself why EASTEY has been a leader in the shrink packaging industry for over 25 years.

STANDARD FEATURES
- Designed to seal most polyolefin, polyethylene, and PVC shrink films
- All-welded main frame from 12 gauge steel
- Seal head casting equipped with head return cylinder
- Stainless steel film clamps hold film in place while sealing
- Utilizes durable and low maintenance hot knife seal system
- Hot knife seal systems available with mushroom (standard), pancake, arrow, or poly inserts
- Dual locking magnet clamps apply even pressure across seal bar
- Adjustable dwell time for better seal control
- Analog temperature control adjustable for a variety of films
- Adjustable product tray accommodates wide variety of product sizes
- Takeaway conveyor can be raised or lowered to center-seal product
- Automatic takeaway conveyor with stainless steel mesh belting
- Heavy duty film roll support and simple film loading
- Adjustable pin perforator provides air evacuation
- Custom two-part epoxy finish resists scratching
- Heavy duty casters for transportation within plant
- Easy to use design requires minimal training and maintenance
- Seal size of 16" x 22" or 16" x 36"
- Maximum film width up to 19"
- Available in 110v or 220v
- Made in the USA

EASTEY®
an ENGAGE Technologies Company

L-SEALERS
PERFORMANCE SERIES





1. ***Hot knife seal head***
   Utilizes low maintenance hot knife seal head

2. ***A variety of seal inserts are available***
   Different films and seal widths: mushroom (standard), pancake, poly, or arrow

3. ***Product Tray***
   Adjustable product tray easily separates film and accommodates variety of product sizes

4. ***Pin Perf***
   Adjustable pin perforator provides air evacuation in film

5. ***Control Panel***
   Simple, easy to use control panel with automatic cycle timing

6. ***Conveyor***
   Takeaway conveyor can be raised or lowered to center the seal on your product

MODEL NUMBER	SEAL DIMENSIONS		MACHINE DIMENSIONS			STANDARD POWER			WEIGHT	SHP WT.
	FRONT	SIDE	WIDTH	HEIGHT	LENGTH	VOLTS	AMPS	PHASE		
EM1622TK	22″ 56 cm	16″ 41 cm	27″ 69 cm	50″ 127 cm	63″ 160 cm	220/110	10/20	1	400 lbs 156 kg	500 lbs 226 kg
EM1636TK	36″ 91 cm	16″ 41 cm	27″ 69 cm	50″ 127 cm	91″ 231 cm	220/110	10/20	1	500 lbs 226 kg	600 lbs 272 kg

EASTEY
an ENGAGE Technologies Company

7041 Boone Avenue North, Brooklyn Park, MN 55428
(763) 428-4846 1 (800) 835-9344
www.eastey.com info@eastey.com

SOLID INK CODING & MARKING SOLUTIONS
EASTEY CASE SEALING & SHRINK PACKAGING EQUIPMENT
AFM SHRINK SLEEVE & LABELING SOLUTIONS
ENGAGE technologies corporation