LT Automatic Stretch Wrapper

Entry level automation with high level features. At 17 RPM, this low to medium volume made in the USA automatic stretch wrapper enables your operation to wrap faster, uses less space and film, and keeps your operators safe. The end result is increased performance.

- 10” color touch screen
- Allen Bradley PLC and drives
- Small footprint makes it perfect for most operations.
- 15 customizable wrap recipes with Cube Technology
- 5 foot infeed and outfeed conveyors
- Conveyor and main frame adjustable 18” – 24” pass heights
- Automatic load height sensing
- Automatic film tail treatment (Clamp, cut, and wipe down)
- Variable turntable speed
- Variable carriage speed
- Safety fencing

Performance features:

CONTROL PANEL

Includes Allen Bradley Micro 800 series PLC. The 10 inch color touch screen makes it easy to program and operate. Includes 15 customizable wrap recipes with Cube Technology.

AUTOMATIC LOAD HEIGHT SENSING AND FILM TAIL TREATMENT

Automatically senses top of load to provide your load with full film coverage. Cut, clamp, and wipe down unit secures the film tail at the end of the wrap cycle to the load to avoid loss of containment at the bottom of the load.

FILM SAVINGS

With 200% fixed pre-stretch included, the LT Automatic guarantees that stretch film will go further which saves money. Our variable pre-stretch option help you save more on film costs by pre-stretching your film up to 400%.

SMALL FOOPRINT

With one of the smallest footprints in its category, the LT Automatic is able to be placed in areas that meet your operations workflow requirements.



LT Automatic Specifications

Performance Capabilities

Production speed:
30-35 loads/hour based on 40”x48”x60” pallet
Max load weight:
4000 lbs.
Max load dimension:
52’ L x 52” W x 82” H (102" Height Optional)
Min load dimension:
36’ L x 36” W x 18” H

Load Handling System

Turntable speed:
7-17 RPM
Turntable overall diameter:
69”
Conveyor speed:
40/60 FPM; 52’’ W; Adjustable 18-24’’pass H

Film Delivery System

Pre-stretch:
Fixed 200%; Optional 150%, 250%, 300%
Reel dimension:
10” D; 20” W

Utilities

Voltage:
480V; 20A; 60Hz;3Ph
Air:
3 CFM 80 PSI